

Webbing slings

DH-LIFTING Webbing slings are made of 100% high tenacity polyester (PES) webbing material manufactured according to EN standards.

These slings have the following advantages:

- Light weight, therefore offering easy handling
- Protection against hand injuries
- Protection against cargo surface damage
- Highly flexible and adaptable to given shapes
- UV-resistant, eliminating material aging or brittleness
- Heat resistant up to 100°C
- Water-resistant fabric, preventing frost damage (down to 40°C)
- Soft sewn eyes (Flat, Becket or Reverse eyes)
- Low elongation



Double Ply Flat Webbing Sling 1Ton - 12Ton

★ Specification:

- Material: 100% High tenacity industrial polyester yarn
- Ply: Double Ply
- With reinforced lifting eyes
- Length Available: 1m to 12m
- Low elongation
- According to EN1492-1+A1:2008
- CE & G.S. certified



ART.NO.	W.L.L. (kg)	7:1 WIDTH inch	7:1&8 WIDTH (mm)	COLOR	WLL in kg at different modes				
					Straight lift	Basket lift	7:45°	Choker hitch	45° 60°
TP-WS-201	1000	1	30	Violet	1000	2000	1400	800	1000
TP-WS-202	2000	2	60	Green	2000	4000	2800	1600	2000
TP-WS-203	3000	3	90	Yellow	3000	6000	4200	2400	3000
TP-WS-204	4000	4	120	Grey	4000	8000	5600	3200	4000
TP-WS-205	5000	5	150	Red	5000	10000	7000	4000	5000
TP-WS-206	6000	6	180	Brown	6000	12000	8400	4800	6000
TP-WS-208	8000	8	240	Blue	8000	16000	11200	6400	8000
TP-WS-210	10000	10	300	Orange	10000	20000	14000	8000	10000
TP-WS-212	12000	12	300	Orange	12000	24000	16800	9600	12000

Four Ply Flat Webbing Sling 2Ton - 24Ton



ART.NO.	W.L.L. (kg)	7:1 WIDTH inch	7:1&8 WIDTH (mm)	COLOR	WLL in kg at different modes				
					Straight lift	Basket lift	7:45°	Choker hitch	45° 60°
TP-WS-401	2000	1	30	Violet	2000	4000	2800	1600	2000
TP-WS-402	4000	2	60	Green	4000	8000	5600	3200	4000
TP-WS-403	6000	3	90	Yellow	6000	12000	8400	4800	6000
TP-WS-404	8000	4	120	Grey	8000	16000	11200	6400	8000
TP-WS-405	10000	5	150	Red	10000	20000	14000	8000	10000
TP-WS-406	12000	6	180	Brown	12000	24000	16800	9600	12000
TP-WS-408	16000	8	240	Blue	16000	32000	22400	12800	16000
TP-WS-410	20000	10	300	Orange	20000	40000	28000	16000	20000
TP-WS-412	24000	12	300	Orange	24000	48000	33600	19200	24000

Endless Flat Webbing Sling 1Ton - 12Ton

★ Specification:

- Material: 100% High tenacity industrial polyester yarn
- Endless Type
- Length Available: 0.5m to 12m
- Low elongation
- According to EN1492-1+A1:2008



ART.NO.	5:1&6:1 WIDTH (mm)	7:1&8:1 WIDTH (mm)	COLOR	WLL in kg at different modes:				
				Straight lift	Basket lift	3-4 point	Choker hitch	As-ss
TP-EWS-01	25	30	Violet	1000	2000	1400	800	1000
TP-EWS-02	50	60	Green	2000	4000	2800	1600	2000
TP-EWS-03	75	90	Yellow	3000	6000	4200	2400	3000
TP-EWS-04	100	120	Grey	4000	8000	5600	3200	4000
TP-EWS-05	125	150	Red	5000	10000	7000	4000	5000
TP-EWS-06	150	180	Brown	6000	12000	8400	4800	6000
TP-EWS-08	200	240	Blue	8000	16000	11200	6400	8000
TP-EWS-10	250	300	Orange	10000	20000	14000	8000	10000
TP-EWS-12	300	300	Orange	12000	24000	16800	9600	12000



DH-LIFTING Round Sling 1Ton - 50Ton

EN 1492-2 : 2000+A1:2008



Round slings are manufactured according to EN1492-2 and have a safety factor of 7:1. The load bearing fibers are wound together to form an endless hank. The working load limit is determined by the number of turns in the hank.

Round slings are manufactured on a round sling machine. Slings made on this machine are more compact as the winding of the yarn is uniform and the tension on each yarn is constant.

Advantages over Round Slings

Round Slings have a high strength to weight ratio.
Wears evenly along the length.
Load bearing fiber protected the sling from the load, giving greater resistance to the wear.
Remove slings from service when the outer cover is damaged and/or the yarn is exposed.

For More Information, Please Visit Us At
www.t-lifting.com



Round Sling

Safety Factor 7:1

According to EN1492-2

ART.NO.	W.L.L. (kg)	WIDTH (mm)	COLOR	WLL in kg at different modes				
				Straight lift	Basket lift	7-11	Choker hitch	2:1
TP-RS-01	1000	45	Violet	1000	2000	1400	800	1000
TP-RS-02	2000	50	Green	2000	4000	2800	1600	2000
TP-RS-03	3000	60	Yellow	3000	6000	4200	2400	3000
TP-RS-04	4000	75	Grey	4000	8000	5600	3200	4000
TP-RS-05	5000	85	Red	5000	10000	7000	4000	5000
TP-RS-06	6000	90	Brown	6000	12000	8400	4800	6000
TP-RS-08	8000	105	Blue	8000	16000	11200	6400	8000
TP-RS-10	10000	115	Orange	10000	20000	14000	8000	10000
TP-RS-12	12000	120	Orange	12000	24000	16800	9600	12000
TP-RS-15	15000	130	Orange	15000	30000	21000	12000	15000
TP-RS-20	20000	130	Orange	20000	40000	28000	16000	20000
TP-RS-25	25000	175	Orange	25000	50000	35000	20000	25000
TP-RS-30	30000	175	Orange	30000	60000	42000	24000	30000
TP-RS-40	40000	220	Orange	40000	80000	56000	32000	40000
TP-RS-50	50000	220	Orange	50000	100000	70000	40000	50000



DH-LIFTING Ratchet Tie Down

400Kg - 10000Kg

EN 12195-2 : 2000



- The width of ratchet tie down produced by DH ranges from "1" to "4".
- Capacity ranges from 400kg to 10,000 kg.
- Varieties of colors can be customized by requirements.



DH-LIFTING 1" Ratchet Tie Down



RATCHET-101



RATCHET-102



RATCHET-103



RATCHET-104



Double J Hook



S Hook

Model	Lashing Capacity	Webbing Width	Min. B.S	B.S of Webbing (Normal)	B.S of Webbing (EN12195-2)	Color	Ratchet Choice
TP-RTD-2501	400daN	25mm	800daN	1000daN	1200daN	Orange/Blue/Yellow/White	Ratchet101/102/103
TP-RTD-2502	500daN	25mm	1000daN	1250daN	1500daN	Orange/Blue/Yellow/White	Ratchet101/102/103
TP-RTD-2503	750daN	27mm	1500daN	1875daN	2250daN	Orange/Blue/Yellow/White	Ratchet104

DH-LIFTING 1.5" Ratchet Tie Down



RATCHET-151



RATCHET-152



RATCHET-153



RATCHET-154



Double J Hook



Swan Hook



Single J Hook



Open Hook

Model	Lashing Capacity	Webbing Width	Min. B.S	B.S of Webbing (Normal)	B.S of Webbing (EN12195-2)	No. of Black Strip	Color	Ratchet Choice
TP-RTD-3501	1000daN	35mm	2000daN	2500daN	3000daN	2	Orange/Blue/Yellow/White	Ratchet151
TP-RTD-3502	1300daN	35mm	2600daN	3250daN	3900daN	3	Orange/Blue/Yellow/White	Ratchet152/153/154

DH-LIFTING 2" Ratchet Tie Down



Double J Hook	Single J Hook	Open Hook	Triangle Ring	Flat Hook	E Fitting	Rotate Hook
2000/3000/4000/5000daN	3000/5000daN	4000/5000daN	5000daN	5000daN	2000daN	5000daN

Model	Lashing Capacity	Webbing Width	Min. B.S	B.S of Webbing (Normal)	B.S of Webbing (EN12195-2)	Color	Ratchet Choice
TP-RTD-3001	1000daN	50mm	2000daN	2500daN	3000daN	Orange/Blue/Yellow/etc	Ratchet201/202/203
TP-RTD-5002	1500daN	50mm	3000daN	3750daN	4500daN	Orange/Blue/Yellow/etc	Ratchet202/203
TP-RTD-5003	2500daN	50mm	4000daN	5000daN	5000daN	Orange/Blue/Yellow/etc	Ratchet202/203/204/205/206
TP-RTD-5004	2500daN	50mm	5000daN	6250daN	7500daN	Orange/Blue/Yellow/etc	Ratchet202/203/204/205/206

DH-LIFTING 3" Ratchet Tie Down



Model	Lashing Capacity	Webbing Width	Min. B.S	B.S of Webbing (Normal)	B.S of Webbing (EN12195-2)	Color
TP-RTD-7501	4000daN	75mm	8000daN	10000daN	12000daN	Orange/Blue/Yellow/etc
TP-RTD-7502	5000daN	75mm	10000daN	12500daN	15000daN	Orange/Blue/Yellow/etc

DH-LIFTING 4" Ratchet Tie Down



Model	Lashing Capacity	Webbing Width	Min. B.S	B.S of Webbing (Normal)	B.S of Webbing (EN12195-2)	Color
TP-RTD-10001	4000daN	100mm	8000daN	10000daN	12000daN	Orange/Blue/Yellow/etc
TP-RTD-10002	5000daN	100mm	10000daN	12500daN	15000daN	Orange/Blue/Yellow/etc

DH-LIFTING Ratchet Tie Down(AS/NZS) 1500Kg - 10000Kg AS/NZS 4380:2001



AS/NZS 4380:2001 Standard Ratchet Tie Down

Model	Lashing Capacity	Webbing Width	Min.B.S	Hook	Color of Webbing	Color of Protector	Ratchet Choice
TP-RTD-AS01	750daN	27mm	1500daN	S Hook/Swan Hook	Blue	Yellow	Ratchet104
TP-RTD-AS02	1500daN	35mm	3000daN	Swan Hook	Blue	Yellow	Ratchet150/153/154
TP-RTD-AS03	2500daN	50mm	5000daN	Swan Hook	Blue	Yellow	Ratchet250/203/204/205
TP-RTD-AS04	5000daN	75mm	10000daN	Swan Hook	Blue	Yellow	Alu.Handle

DH-LIFTING Ratchet Tie Down(WSTDA)

Working Load Limit: 3333lbs Breaking Load Limit: 10000lbs

WSTDA-T-1



Model:TP-RTD-US01

★ Specification

- ◆ Standard:WSTDA-T-1
- ◆ Width:2" (50mm)
- ◆ Working Load Limit: 3333lbs
- ◆ Assembly Breaking Strength:10000lbs
- ◆ Webbing Breaking Strength:12500lbs
- ◆ Safety Factor: 3:1
- ◆ Webbing Color: Yellow/ etc.
- ◆ Ratchet:Ratchet202/203/204/205
- ◆ Normal Size: 2"x27" , 2"x30"



DH-LIFTING Ratchet Tie Down(WSTDA)

Model: DH-RTD-US02

★ Specification

- ◆ Standard: WSTDA-T-1
- ◆ Width: 2" (50mm)
- ◆ Working Load Limit: 1500lbs
- ◆ Assembly Breaking Strength: 4500lbs
- ◆ Webbing Breaking Strength: 6000lbs
- ◆ Safety Factor: 3:1
- ◆ Webbing Color: Yellow/Grey/etc
- ◆ Ratchet: Ratchet201
- ◆ End Fitting: E-Fitting



Model: DH-RTD-US03

★ Specification

- ◆ Standard: WSTDA-T-1
- ◆ Width: 2" (50mm)
- ◆ Working Load Limit: 1000lbs
- ◆ Assembly Breaking Strength: 3000lbs
- ◆ Webbing Breaking Strength: 6000lbs
- ◆ Safety Factor: 3:1
- ◆ Webbing Color: Yellow/Grey/etc
- ◆ Ratchet: Cam Buckle
- ◆ End Fitting: E-Fitting



Model: DH-RTD-US04

★ Specification

- ◆ Standard: WSTDA-T-1
- ◆ Width: 4" (100mm)
- ◆ Working Load Limit: 5400lbs
- ◆ Assembly Breaking Strength: 16200lbs
- ◆ Webbing Breaking Strength: 20000lbs
- ◆ Safety Factor: 3:1
- ◆ Webbing Color: Yellow/etc
- ◆ Ratchet: Alu. Handle
- ◆ End Fitting: Double J Hook/Flat Hook/etc



DH-LIFTING Ninjaline & Slackline



71-75 Shelton Street
Covent Garden London
WC2H 9JQ
+44 0204 511 2432
sales@dh-lifting.co.uk

RATCHET TIE DOWN